

# I.T.E. Power Supply

## 24 Watt Series | Desktop Type

**Features**

- IEC/EN/UL 62368-1 & 60950-1
- 100-240VAC Universal Input
- Single Output to 24W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Modified and Custom Design Available
- Green Mode  
CEC, DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCan & GEMS Level VI, No Load Power Consumption Less Than 0.075W


**Model**

Model	O/P Voltage	O/P Current	Watt
ATS024T-□050	5.0V	4.00A	20.00W
ATS024T-□060	5.9V	3.50A	20.65W
ATS024T-□061	5.9V	4.00A	23.60W
ATS024T-□070	7.0V	3.00A	21.00W
ATS024T-□075	7.5V	3.00A	22.50W
ATS024T-□090	9.0V	2.50A	22.50W
ATS024T-□120	12.0V	2.00A	24.00W
ATS024T-□150	15.0V	1.60A	24.00W
ATS024T-□240	24.0V	1.00A	24.00W
ATS024T-□480	48.0V	0.50A	24.00W

ATS024T-□XXX  
 P : C6 / C14 ←  
 A : C8 → O/P Voltage

**Input**

Voltage	100-240VAC
Line Frequency	50/60Hz
Current	0.58A Max.
Protetction	Internal Primary Current Fuse
Configuration	IEC60320/C6,C8,C14

## ATS024T Series

### Output

Load Regulation	±5% ( Typical )
Ripple & Noise	2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	22AWG / 20AWG / 18AWG / 16AWG
Ferrite Core	No (Optional)

### Safety Approvals

CB / UL / cUL / FCC / GS / CE / PSE / BSMI / CCC / RCM / LPS
--

### Electrical

Topology	Switching Flyback
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	0.25mA
Efficiency	DoE Level VI, Energy Star, ErP Stage 2, CoC Tier 2, NRCan & GEMS Level VI Certified
EMC Standards	EN55032
	EN61000-3-2,3
	EN55024
MTBF	300,000 Calculated Hours at 25°C, by Telcordia SR-332

### Environmental

Operating Temperature	0 to +40°C
Storage Temperature	-20 to +80% RH
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

### Mechanical

Case Dimension	C6 & C14 : L100 x W50 x H33(mm)
	C8 : L88 x W50 x H34(mm)
Weight	166g (Ref.)